

BS30

2 Stroke Rammer



**WACKER
NEUSON**
all it takes!



The specialist rammer for pipe supports

BS30 is the specialist rammer to compact pipe supports in trenches professionally. The low weight, compact dimensions and the ability to perform at full capacity in a tilted position make the BS30 the only choice for these jobs. It is powered by the exclusive Wacker Neuson WM80 motor.

- The two-cycle engine enables operation at every angle. (Four-cycle engines can only be tilted up to a maximum of 20°.)
- The low weight and compact dimensions make handling easier, especially when used at an angle and in confined spaces.
- The BS30 is also suitable for: Reinforcing the edges of sidewalks and bikeways, installing drainage systems.

BS30 Technical specifications

BS30

Operating data

Operating weight	32 kg
Ramming shoe size (WxL)	150 x 264 mm
L x W x H	620 x 370 x 980 mm
Percussion rate max.	820 blows/min
Stroke at the ramming shoe	42 mm
Impact force	10 kN
Engine / Motor	
Engine / Motor type	Air-cooled single-cylinder two-cycle gasoline engine
Engine / Motor manufacturer	Wacker Neuson
Engine / Motor	WM80
Displacement	80 cm ³
Fuel consumption	0.9 l/h
Rated performance	1.5 kW
at rpm	4,400 rpm
Tank capacity	2.2 l
Gasoline / oil mixture	1:50
CO ₂ (NRSC) *	1,113 g/kWh

*Determined value of the CO₂ emission during engine certification without consideration of the application on the machine.

Please note: that product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the stated power may vary due to specific operating conditions. Subject to alterations and errors excepted. Applicable also to illustrations.
Copyright © 2021 Wacker Neuson SE.